

Model	GRO-150	GRO-250	GRO-500	GRO-700	ES-1600	ES-3200	ES-4800	ES-6400	ES-8000	ES-9600
Output gpd/mday	150/.6	250/.94	500/1.9	700/2.7	1,600/6.1	3,200/12.1	4,800/18.2	6,400/24.2	8,000/30.3	9,600/36.4
Product Flow (gph)	6.00	10.20	20.40	28.80	66.00	132.00	198.00	264.00	330.00	396.00
Reject Flow (gph)	0.23	0.31	0.52	0.52	1.10	2.20	2.20	2.70	3.00	4.40
Recovery Rate	30%	35%	40%	48%	50%	50%	60%	62%	65%	60%
Membrane Quantity	1	1	2	3	1	2	3	4	5	6
Membrane Size	2.5"x14"	2.5"x21"	2.5"x21"	2.5"x21"	4"x40"	4"x40"	4"x40"	4"x40"	4"x40"	4"x40"
Pump HP	1/3	1/3	1/3	1/3	3/4	3/4	3/4	3/4	1.5	1.5
Inlet Connection	3/8"	3/8"	3/8"	3/8"	3/4"	3/4"	3/4"	3/4"	1"	1"
Product Connection	1/4"	1/4"	1/4"	1/4"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"
Reject Connection	1/4"	1/4"	1/4"	1/4"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"
Weight (Lbs/Kilo)	40/18	50/23	58/26	66/30	180/82	200/91	220/100	240/109	260/118	280/127
Size (L" x W" x H")	20x30x20	20x30x20	20x30x20	20x30x21	44x44x68	44x44x68	44x44x68	44x44x68	44x44x68	44x44x68
Packaging	Carton	Carton	Carton	Carton	Pallet	Pallet	Pallet	Pallet	Pallet	Pallet

* Output is based on 60Hz power, 70°F Temperature, up to 1,000 mg/l TDS, 8.0 pH

SPECIFICATIONS

